

हर रंग में
मोहे रंग दे!

अपने घर और ज़िंदगी में लाएं Vivid का जादू



VIVID EXTERIOR EMULSION

Mastertouch Vivid Exterior Emulsion is a high quality modified acrylic emulsion specially designed for use in dry or less humid climate & provides good algae & fungal resistance. It has a special anti-peel formula that gives excellent resistance against chalking & peeling.

Available in 1, 4, 10 & 20 L



FEATURES



Rich & smooth
matt finish



Water
resistant



Anti peel
formula



Anti fungal
protection



Good
washability



Non-flammable
No added lead,
mercury, chromium

SUBSTRATE

All kind of well-prepared exterior plasters, concrete and masonry surfaces.

COVERAGE

50-70 Sq. Ft / Ltr / 2 Coat

(Actual Coverage may depend on factors like Surface Preparation, Method of Application, Dilution etc.)

SHELF LIFE

36 months from the date of manufacture in original tightly closed container.

PRODUCT BENEFIT

Rich Aesthetic Look.
Smooth and Matt Finish.
Value for Money.
Easy Application.
Eco Friendly.

TECHNICAL DATA	
PARAMETERS	SPECIFICATIONS
Nature	White Free Flowing Liquid
Dilution ratio	750 ml of clean water/ 1L of emulsion
Application	By Brush, Roller or Spray
Drying time	Surface dry: 30 min. Re - Coatability: 6-8 hrs.
Sheen level	2-3 at 60° GH
VOC Content	Low VOC
Stability of thin paint	To be used within 24 hrs.

SUBSTRATE PREPARATION

- New masonry surfaces must be allowed to cure completely. It is recommended to allow 28 days as the curing time for new masonry surfaces. For repairing plaster surface use WallEX Ready Mix Plaster (for guidelines refer WallEX Ready Mix Plaster TDS).
- Ensure the surface is completely free from dirt, dust, loose paints, powdery residue, oil greases or any other contaminants.
- Any previous growth of fungus, algae or moss needs to be removed thoroughly by vigorous wire brushing and cleaning with water.
- Before application any crack and minor damages on surface should be repaired with WallEX Crack Filler (for guidelines refer WallEX Crack Filler TDS).

PRIMER APPLICATION PROCESS

- Apply one coat of Mastertouch Exterior Primer with proper dilution and allow to dry for 4-6 hrs. before top coat application. (For guidelines refer Mastertouch Exterior Primer TDS).
- Application can be done by using brush, roller or spray.

TOPCOAT EMULSION APPLICATION PROCESS

- On primer application, apply two coats of Mastertouch Vivid Exterior Emulsion with proper dilution.
- Keep 6-8 hrs drying time between two coats.
(Drying time may vary according to the temperature and humidity.)
- Application can be done by using brush, roller or spray.
- For darker shades require additional third coat.

USAGE PRECAUTIONS

- Do not alter water addition than recommended level.
- For better performance two coat application is required.
- Vivid Exterior Emulsion contains non-toxic material but still, it is important to wear a safety kit while mixing and handling paint.

POST PAINTING CARE

- For the best performance of the paints, ensure proper washing and cleaning of algae and fungal growth.
- Washing should be done on regular interval of six months.