

## STANDARD GYPSUM PLASTERBOARD

GYPEX Gypsum plasterboard Standard consists of a core of set gypsum surfaced with specifically manufactured paper firmly bonded to the core. It is designed to be used without the addition of plaster of walls, ceilings or partitions and provides a surface suitable to receive either paint or paper.

### PRODUCT DESCRIPTION

**PRODUCT:** Gypsum plasterboards are prefabricated, ready-to-install calcium sulphate boards

COMPOSITION	<ul style="list-style-type: none"><li>Gypsum, additives, and firmly bonded strong paper liners</li></ul>
BOARD COLOUR	<ul style="list-style-type: none"><li>Ivory face paper</li><li>Brown back side paper</li></ul>
FEATURES	<ul style="list-style-type: none"><li>Easy application</li><li>Time saving</li><li>High surface quality</li><li>Fire resistance</li><li>Non-combustible</li><li>Acoustic property</li><li>Thermal properties</li><li>Low cost</li></ul>

### TECHNICAL ANALYSIS (INTERNAL)

THICKNESS (mm)	SIZE (mm)	EDGE TYPE
9.5	1220X 1830 1220 X 2440	Tapered/Square
12.5	1220 X 1830 1220 X 2440	Tapered/Square
15	1220 X 1830 1220 X 2440	Tapered/Square

## GUIDANCE FOR USE

**GENERAL**

- It is important to observe appropriate health and safety legislation when working on site i.e., personal protective clothing and equipment, etc.

**HANDLING**

- Manual offloading of this product should be carried out with care to avoid unnecessary strain.

**CUTTING**

- This product may be cut using a plasterboard saw or by scoring with a sharp knife.
- Holes for switch or socket boxes should be cut out before the boards are fixed using a utility saw or sharp knife. Mixing should be carried out in a clean tray or bucket.
- When cutting boards, power and hand tools should be used with care and in accordance with the manufacturers' recommendations.
- Power tools should only be used by people who have been instructed and trained to use them safely.
- Appropriate personal protective equipment should be used.

**FIXING**

- Fix boards with decorative side out to receive joint treatment or a skim plaster finish.
- Install fixings not closer than 13mm from cut edges and 10mm from bound edges.
- Position cut edges to internal angles whenever possible, removing paper burrs with fine sandpaper.
- Locate boards to the centre line of framing where this supports board edges or ends.

**USAGE PRECAUTION**

- Minimise dust generation when sawing or sanding in poorly ventilated places.
- Avoid eye contact.
- Plasterboards will not support body weight in between rafters, joints or frame members.
- When working with individual boards, only work from a single pallet, not a stack.

## ■ STORAGE INSTRUCTIONS

- Store on pallets supplied in dry conditions.
- To maintain stability place pallets on firm level ground and ensure that stacks are both level and vertical.
- Keep away from water and damp area.

## ■ HEALTH & SAFETY INFORMATION

- It contains only eco-friendly fillers and additives. In case of eye contact, kindly wash with clean water at least for 15 minutes and seek medical help and keep it out of children reach.

**Disclaimer:** Technical information is based on knowledge and experience of accurate results. These results refer to the long-term application of the product in practice. Recommendations and suggestions are listed for guidance only. Since site conditions during the applications are beyond the manufacturer's control, hence it is also the responsibility of the end-user to ensure that the content in their possession is the latest case.