

ACRYLIC TEXTURE

Acrylic texture is trowel applied synthetic grooved finish Texture. The product is formulated with modified acrylic emulsion and marble texturizing sand. Used for decoration and long-term protection. It has unique textured pattern which can be used for interior and exterior surface.

PRODUCT DESCRIPTION

PRODUCT: Acrylic texture is Scratch Finish texture. It is formulated with high quality acrylic modified resin with selected marble texturizing sands which is designed as intermediate coating.

COMPOSITION	Acrylic emulsion, marble sand, Additives
APPEARENCE	White viscous material
AVAILABLE IN	Acrylic texture category – Small, Medium, Large
FEATURES	<ul style="list-style-type: none"> • Aesthetic looks for Interior and exterior walls • Finish – Horizontal, vertical, swirl, rainfall • Easy to apply • Lasts long • Excellent workability • Low maintenance
BENEFITS	<ul style="list-style-type: none"> • Anti-algal • Hides cracks • UV resistance • Tough textured • Plaster protection

TECHNICAL ANALYSIS (INTERNAL TEST METHOD)

PARAMETERS	SPECIFICATIONS
Appearance	White Viscous Form
pH	8 - 10
Surface Drying Time	30 to 60 min
Gloss level	Matt when dry
Solid Content	Min. 80%
Wet Density	2.00 -2.2 g/ml
Adhesion Strength	>1 MPa

GUIDANCE FOR USE

SUBSTRATE	<ul style="list-style-type: none">• Old / New Concrete surfaces• Interior and Exterior Wall• Asbestos cement sheets.• Cement /Lime/Sand renderings
SUBSTRATE PREPARATION	<ul style="list-style-type: none">• New masonry surfaces must be allowed to cure completely. It is recommended to allow 28 days as the curing time for new masonry surfaces.• Ensure the surface is completely free from all dirt, loosely held plaster, powdery residue, oil grease or any other contamination. Any previous growth of fungus, algae or moss needs to be removed thoroughly by vigorous wire brushing and cleaning with water.
DIRECTION OF USE	<ul style="list-style-type: none">• Primer Application- Prime is recommended for repainting or chalky substrate, not on new surfaces.• Texture Application – Apply one coat of acrylic texture with trowel and allow to dry for 24 hours.• Recommended tool – Plastic trowel.• Thinning – If required, use maximum 2% of fresh water for better consistency.
COVERAGE	<ul style="list-style-type: none">• 1 to 1.5 Sq. ft./ kg on plain surface (Or depending on substrate conditions)
USAGE PRECAUTIONS	<ul style="list-style-type: none">• Do not apply when ambient temperature is less than 10°C or if the temperature.• More than 2% Thinning is not advisable.• Do not keep material open for a long time.• Product cannot be applied on surfaces/substrates that are subjected to continuous seepage or dampness.• Stir well before use.
PACK SIZE	<ul style="list-style-type: none">• 25 Kg, 30 Kg
SHELF LIFE	<ul style="list-style-type: none">• 6 Months

SAFETY FEATURES

- Store the bag with the cable tie tightly closed in an upright position, in a cool, dry place.
- Keep out of reach of children and away from eatables.
- May be harmful if swallowed. In case of ingestion seek immediate medical attention.
- Wear eye protection during application. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- In case of skin contact immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists.
- In the event of spills, contain spillage using sand or earth.
- No added Lead, Mercury, or Chromium compounds.

Disclaimer: Technical information is based on knowledge and experience of accurate results. These results refer to the long-term application of the product in practice. Recommendations and suggestions are listed for guidance only. Since site conditions during the applications are beyond the manufacturer's control, hence it is also the responsibility of the end-user to ensure that the content in their possession is the latest case.