

WALL PUTTY

Wall Putty is a cement-based polymer modified wall putty specially developed as a base coat to cover unevenness and pinholes on plastered, mortar wall and ceiling to make the surface wall ready for primer and paint application. Wall Putty fills the imperfections, cracks, and faults on the surface.

PRODUCT DESCRIPTION

PRODUCT: White cement-based fine powder for perfect smooth finish. It is applied on the wall before the final paint so that the life of the paint increases. Wall Putty form an excellent bonding to the base concrete or plastered surfaces.

COMPOSITION	White cement, selected fillers, polymers
COLOUR	White fine powder
TESTS	Tested according to IS-4031, EN-1015, & Internal test methods
FEATURES	<ul style="list-style-type: none">• Aesthetic look for ceiling, Interior & Exterior walls• Protect expensive paint from dampness & peeling• Colour tone of paint is maintained• Avoid frequent repainting• Excellent workability• UV Resistance
USES	<ul style="list-style-type: none">• Bonding to the base plaster• Reduce Paint consumption• Highly water resistant• Long lasting- Smooth finish• High Durability• Save Time• Cost-Effective

TECHNICAL ANALYSIS (CONFORMS TO IS-4031, EN-1015, & INTERNAL TEST METHOD)

TECHNICAL DATA	
PARAMETERS	SPECIFICATIONS
WHITENESS	> 85 %
CONSISTENCY	30 – 45 %
POT LIFE	> 90 minutes
SETTING TIME	30 – 600 minutes
DENSITY	1.3 -1.5 g/ml

MECHANICAL PROPERTIES**PULL-OFF STRENGTH (AFTER 14 DAYS)****DRY ADHESION** > 0.80 MPa**COMPRESSION & FLEXURAL STRENGTH (AFTER 28 DAYS)****COMPRESSIVE STRENGTH** 7 – 12 MPa**FLEXURAL STRENGTH** > 1.5 MPa**WATER PROPERTIES****WATER ABSORPTION (AFTER 28 DAYS)** < 0.20 kg/m²min^{0.5}**WATER RETENTIVITY** > 95 %**GUIDANCE FOR USE**

- | | |
|------------------------------|--|
| SUBSTRATE | <ul style="list-style-type: none">• Concrete/Mortar walls (internal and external)• Ceilings• Application before painting• It can be used any type of surface like concrete, rendered wall, hollow block• Precast walls, concrete ceilings, calcium silicate bricks etc. |
| SUBSTRATE PREPARATION | <ul style="list-style-type: none">• Clean loose particles, dirt, grease and traces of foreign materials from the surface, if necessary, by using wire brush/sand paper or by chipping.• For loose plaster areas or floors/wall which are not even, then remove the defective material and re-plaster the area with Home Sure Ready-Mix Plaster to make them even. |
| MIXING | <ul style="list-style-type: none">• Take approx.300-450 ml of clean water for 1 Kg of HomeSure Wallputty in a clean bucket. It is very important that add material into water and not vice versa.• Stir continuously for 3-5 minutes by using mechanical stirrer or by hand to obtain a homogeneous lump-free paste.• Allow the resultant paste to stand for about 10 minutes for the additives to dissolve.• Re-mix again for about 2 Minutes. The mixture is now ready to apply. |
| APPLICATION | <ul style="list-style-type: none">• Dampen the surface to be plastered with clean water. Allow excess water to drain off.• Clean loose particles, dirt from the surface by using painter patra/blade.• Using paint patra/ blade, apply 1st coat of wallputty to a thickness of 1-2mm.• Cover all undulations and rough surface in 1st coat.• Allow the surface to dry for at least 4 to 5 hours.• Apply 2nd coat of 0.5-1 mm after the 1st coat completely dried.• Total thickness of wallputty should not exceed than 2-3 mm.• Check finishing of wall after 24 hours. |

COVERAGE	<ul style="list-style-type: none">• 10-15 Sq. Ft./1 kg bag at 2-3 mm thickness on plain surface (Or depending on substrate conditions).
USAGE	<ul style="list-style-type: none">• Do not add more water than recommended.
PRECAUTIONS	<ul style="list-style-type: none">• Maximum thickness should not more than 2-3 mm.• HomeSure Wallputty contains non-toxic material but still, it is important to wear a safety kit when mixing and handling.

STORAGE INSTRUCTIONS

- Store in cool, dry, and well-ventilated place away from heat source or direct sunlight.
- Keep away from water and damp area.
- Avoid using partially used material; open bags with partially used material should be kept in a bag with its mouth tied tightly with string to prevent lump formation.
- As temperature, humidity, water addition and other parameters vary from site to site; the above information should be treated as general guidelines.

HEALTH & SAFETY INFORMATION

- It contains only eco-friendly fillers and additives. However, being cement based, it is alkaline and hence it is advisable to avoid direct eye and skin contact with this. In case of eye contact, kindly wash with clean water at least for 15 minutes and seek medical help and keep it out of children reach.

Disclaimer: Technical information is based on knowledge and experience of accurate results. These results refer to the long-term application of the product in practice. Recommendations and suggestions are listed for guidance only. Since site conditions during the applications are beyond the manufacturer's control, hence it is also the responsibility of the end-user to ensure that the content in their possession is the latest case.