

MASTERTOUCH LUSH INTERIOR EMULSION

MasterTouch Lush Interior Emulsion is an economical interior wall paint that provides a smooth finish with a rich look. Crafted with quality pigments and acrylic binders, it delivers decent coverage, good colour retention, and resistance to fungus, making it a budget-friendly solution for durable and attractive interiors.

■ PRODUCT DESCRIPTION

FEATURES

- Superior to Cement Paints
- Excellent Whiteness and Opacity
- Cost-Effective Coverage
- Eco-Friendly Formula

BENEFITS

- Enhanced Aesthetics
- Cost-Effective Solution
- Durable Performance
- Good Colour Retention

■ TECHNICAL ANALYSIS (INTERNAL TEST METHOD)

TECHNICAL DATA

Nature	White Free Flowing Liquid
Dilution ratio	400-500 ml of clean water/ 1l of emulsion
Application	By Brush, Roller, and Spray
Coverage	85-100 Sq. Ft / Ltr / 2 Coat (Actual Coverage may depend on factors like Surface Preparation, Method of Application, Dilution etc.)
Drying time	Surface dry: 30 min. ReCoatability: 4 hrs.
Sheen level	Soft
VOC Content	Low VOC
Stability of thin paint	To be used within 24 Hrs
Shelf-Life	12 months from date of manufacture in original tightly closed container

GUIDANCE FOR USE

SUBSTRATE	<ul style="list-style-type: none"> • All types of well-prepared interior plasters, concrete and masonry surfaces
SUBSTRATE PREPARATION	<ul style="list-style-type: none"> • New masonry surfaces must be allowed to cure completely. It is recommended to allow 28 days as the curing time for new masonry surfaces. For repairing plaster surface use Walplast BuildWell Ready Mix Plaster (for guideline refer Walplast BuildWell Ready Mix Plaster TDS). • Ensure the surface Should be completely free from dirt, dust, loose Paints, powdery residue, oil greases or any other contamination. • Any previous growth of fungus, algae or moss needs to be removed thoroughly by vigorous wire brushing and cleaning with water. • Before application any crack and minor damages on surface should be repaired with Walplast HomeSure Crack Filler (for guideline refer Walplast HomeSure Crack Filler TDS).
PRIMER APPLICATION PROCESS	<ul style="list-style-type: none"> • Apply one coat of Mastertouch Prime Interior Primer with proper dilution and allow to dry for 4-6 hrs. (for guideline refer Mastertouch Prime Interior Primer TDS) • Apply 2 Coat of Walplast HomeSure Wall Putty (for guideline refer Walplast HomeSure Wall Putty TDS). Ensure surface smoothness and levelling by sanding with sandpaper 180 and wipe clean. • Apply one coat of Mastertouch Prime Interior Wall Primer with proper dilution and allow to dry for 4-6hrs. before topcoat application. • Application can be done by using brush, roller, spray.
TOPCOAT DILUTION	<ul style="list-style-type: none"> • Dilute 1 litre of paint with 400-500 ml of clean water.
TOPCOAT EMULSION APPLICATION PROCESS	<ul style="list-style-type: none"> • On primer application, apply two coats of Mastertouch Lush Interior Emulsion with 40-50% water dilution. • Take 4-6 hr drying time between two coats. (Drying time may vary according to the temperature and humidity.) • Application can be done by using brush, roller, spray. • For darker shades require additional 3rd coat for better hiding and appearance.
USAGE PRECAUTIONS	<ul style="list-style-type: none"> • Do not alter water addition than recommended level. • For better performance two coat application is required. • Mastetouch Lush Interior Emulsion contains non-toxic material but still, it is important to wear a safety kit while mixing and handling Paint.
POST PAINTING CARE	<ul style="list-style-type: none"> • For the best performance of the paints, ensure proper washing and cleaning of algae and fungal growth. • Washing should be done on regular intervals of six month.

STORAGE INSTRUCTIONS

- Store in cool, dry, and well-ventilated place away from heat source or direct sunlight.
- Shake well before used and do not over or under dilute the material.
- Keep the container tightly closed to prevent drying.
- Keep the container in upright position.
- As temperature, humidity, water addition and other parameters vary from site to site; the above information should be treated as general guidelines.

SPECIAL NOTE

Following things need to check before application.

1. Moisture content of wall (ideal range Below 12%)
2. pH value of wall surface (should be alkaline in nature)

HEALTH & SAFETY INFORMATION

- Keep it out of children reach and away from eatables.
- Do not breath vapour or spray. It is recommended to wear suitable nose pad during application.
- Wear eye protection during application
- Please avoid direct eye and skin contact. In case of eye contact, kindly wash and clean with plenty of water and seek medical help.
- In case of skin contact immediately wash with soap and water, if irritation develops, please get medical attention.
- No added lead, Mercury, and chromium compound.

Disclaimer: Technical information is based on knowledge and experience of accurate results. These results refer to the long-term application of the product in practice. Recommendations and suggestions are listed for guidance only. Since site conditions during the applications are beyond the manufacturer's control, hence it is also the responsibility of the end-user to ensure that the content in their possession is the latest case.